

ORDER SUBMITTAL INFORMATION

PRODUCT DATASHEET



TEMPERATURE RISE CORE

Steel Sheet Gauge: 16 / 18 / 20

Steel Type: Galvanealed A40 or A60

Fire Rating: up to 3 Hours

Edge Design: Beveled or Square edge

Thickness: 1 3/4 / 2 1/4

Width: 2'0" / 2'6" / 3'0" / 3'6" / 3'8" / 4'0"

Height: 6'8" / 7'0" / 8'0"

Hinge Prep: Variable Hinge Location

*Special height, width and thickness are available upon requests, please contact office.

ORDER SUBMITTAL INFORMATION


PRODUCT DATASHEET

16 GAGE STEEL END CHANNELS

WELDED TO
BOTH FACE SHEET


INVERTED TOP
AND BOTTOM

OPTIONAL TOP
AND BOTTOM CAPS ARE AVAILABLE



CLOSER REINFORCEMENT
(OPTIONAL)


14 GAGE STEEL CHANNEL
20" LONG



LOCK PREPARATION

4-1/2" X .134 HIGH, STANDARD
OR HEAVY WT. FULL MORTISE
HINGE PREPS

NON-HANDED




CLOSURE
PLATES

LOCK PREPARATION
GOV 86-4 MOTISE TYPE

ANSI A115.1
2-3/4" BACKSET


SIMILAR TO DETAIL
LESS FACE CUTOUT

SIMILAR TO DETAIL
LESS ALL CUTOUTS
AND REINFORCEMENT



LOCK PREPARATION
GOV 160/161 CYLINDRICAL TYPE

ANSI A115.2
2-3/4" BACKSET



CORE

SOLID MINERAL CORE
BONDED TO BOTH
FACE SHEETS

